INSOPAINT MASONRY

1. PRODUCT AND COMPANY IDENTIFICATION

1.01 Product Code:

1.02 Product Name: InsOpaint Masonry

1.03 Synonyms: InsOpaint Exterior Masonry Paint

1.04 Intended Use: To Insulate and Waterproof exterior walls. 1.05 Manufacturer/Supplier:

Thermilate Technologies Ltd.

14 Longbow Close

Pennine Business Park HUDDERSFIELD West Yorkshire

HD2 1GQ

1.07 Contact: **Operations Director** +44 0845 680 6124 1.08 Phone Number: 1.09 Emergency Phone Number: +44 0845 680 6124

1. PRODUCT AND COMPANY IDENTIFICATION

Vapor Pressure Weight % Hazardous componenets

Titanium Dioxide (d) 13463-67-7 10mg/m3 10mg/m3 None N/A 5 - 15 25 - 35 Calcium Carbonate (d) 1317-65-3 10mb/m3 10mb/m3 None N/A

(d) Hazardous as dust when product is sanded

Carcinogenicity NO larc Monographs NO OSHA

Regulated NO

1.06 Address:

3. PHYSICAL/CHEMICAL CHARACTERISTICS

3.01 Boiling range: Not applicable - water based material.

3.02 Kilograms per litre: 1.2 3.03 Specify gravity (H20=1) 1.4

3.04 Vapour density: Lighter than air. 3.05 Evaporation rate: Slower than ether.

3.06 Solubility in water: Yes 3.07 Appearance and odour: N/A

4. FIRE & EXPLOSION HAZARD DATA

4.01 Flash point: Not applicable. 4.02 Method used: Not applicable.

4.03 Flammable limits in air by volume: Lower - not applicable Higher - not applicable. 4.04 Extinguishing media: Foam, Alcohol foam, CO2, Dry Chemical, Water Fog, 4.05 Special fire fighting procedures: Keep people away. Do not enter confined fire space without

proper protective equipment including NIOSH approved

self-contained breathing apparatus.

4.06 Unusual fire and explosive hazards: Cool closed container with water. Closed containers may explode

when exposed to extreme heat. During emergency conditions, overexposure to decomposition products may cause a health hazard.

Symptoms may not be immediately apparent. Obtain medical

attention.

SHEET

INMA

INSOPAINT MASONRY

5. REACTIVITY DATA

5.01 Stability:

5.02 Conditions to Avoid:

5.03 Incompatibility (Material to Avoid):

5.04 Hazardous Decomposition or byproducts:

5.05 Hazardous Polymerization:

Stable.

None.

None.

None.

Will not occur.

6. HEALTH HAZARD DATA

6.01 Inhalation health risks and symptoms of exposure:

6.02 Skin and eye contact health risks and symptoms of exposure:

6.03 Skins absorption health risks and symptoms of exposure:

6.04 Ingestion health risks and symptoms of exposure:

6.05 Health hazards (acute & chronic) including target organs:

6.06 Medical conditions generally aggravated by exposure:

6.07 Emergency and First aid procedures.

Vapours or mists can cause drowsiness, cough, bronchitis, blurred vision, irritation of mucous, nausea, headache, dizziness, weakness and loss of coordination.

May cause irritation.

May cause irritation.

May cause headache, gastrointestinal irritation, nausea, vomiting and diarrhoea.

This product may contain some material which at a normal low level should not present a problem.

Any respiratory or skin condition may be aggravated.

Inhalation: Remove to fresh air.

Eyes: Flush immediately with water. Consult physician if irritation

persists.

Skin: Remove with soap and water. remove contaminated clothing. **Ingestion:** Drink 1 to 2 glasses of water to dilute. DO NOT induce vomiting because aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Consult physician or Poison Control Centre immediately. Treat symptomatically.

7. PRECAUTIONS FOR SAFE HANDLING AND USE

7.01 Steps to be taken in case material is realease or spilled:

7.02 Waste disposal method:

7.03 Precautions to be taken in handling and storage:

7.04 Other precautions:

Keep unnecessary people away. Ventilate enclosed spaces and avoid breathing vapours. Wear protective equipment observing precautions on this sheet. Contain and soak up spills with inert material (such as clay, sand, etc.)

Place in non-leaking containers, seal tightly and label properly for disposal. A health hazard may still exist since absorbent materials will only absorb liquid; they will not absorb vapours. Observe all national and local regulations concerning disposal of hazardous waste.

Keep containers closed when no in use. Store and use only in well ventilated areas. Avoid breathing vapours or spray mist. Avoid eye or skin contact. Wash thoroughly after handling. Never transfer material to an unlabelled container.

Read and observe precautions on product label and this sheet. Keep out of reach of children. Empty containers may be hazardous from residues of product and vapour and all caution of this sheet apply them.

INMA 2.13

SHEET

INSOPAINT MASONRY

8. CONTROL MEASURES

8.01 Respiratory information:

8.02 Ventilation:

8.03 Eye protection:

8.04 Other protective clothing or equipment:

8.05 Work/hygienic practices:

None required under normal conditions. Filter recommended to remove solid airborne particles of over spray during spray application. Not for use in confined areas. Use only with adequate ventilation. Face shield recommended for spray application.

Identity, hazard warning, name and address of responsible VOC 0.50 gr/l maximum.

Wash hands before eating, drinking, smoking or using the bathroom.

9. OTHER INFORMATION

This information should be used as a supplement to other information obtained to make independent judgement of suitability and to ensure proper use and protect the health and safety of employees.

Judgement as to the suitability of the information herein for the purchaser's purposes are necessarily purchaser's responsibility. Therefore although reasonable care has been taken in the preparation of such information, Thermilate Technologies Ltd extends no warranties, makes no representations and assumes no responsibility as to the accuracy of suitability of such information for application to purchasers intended purpose or for consequences of its use.



Prepared by Thermilate Technologies Ltd

Dated: 8th Mar 2013 Revised: INMA.2.13 Reviewed: N/A

This Product Data Sheet supersedes all other previously dated sheets for this product.

INMA 2.13

SHEET